

Scanfob® 3002i Bluetooth Barcode Scanner Specifications

SKU: OPN3002i-SF

PHYSICAL	
Power Source	Micro USB/Battery
Battery Option	Embedded
Battery Type	Lithium-Ion polymer rechargeable (600 mAH)
Charging Method	Micro USB
Charge Cycles	10,000
Charging Time	2.5 hours
Operating Time	12 hours with average scanning, 30 hours with light scanning
Dimensions	83mm x 36mm x 22mm (3.27" x 1.42" x 0.85")
Weight	59 g (2 oz)
Memory RAM	1 MB
Memory FlashROM	1 MB
Keys	1 scan button, 1 function button
Real Time Clock	Quartz RTC
Microprocessor	32 bit
INTERFACE	
Bluetooth	HID, SPP, MFi, BLE
USB	Mini USB

Batch Mode	Yes
ENVIRONMENT	
Operating Temperature	0-50 °C (32-122 °F)
COMPATIBILITY	
Operating Systems	Mac, Windows, iOS, Android
Barcode Types	<p>Barcode 1D : UPC/EAN/JAN (standard, composite, addon), Code 39, Codabar (NW7), Industrial 2 of 5, Interleaved 2 of 5, Code 128, Code 93, IATA, MSI/Plessey, UK/Plessey, Telepen, Code 11, Matrix 2 of 5, JPN, GS1Databar (Limited,Expanded, Composite),GS1-128 (standard,composite)</p> <p>Barcode 2D: PDF417, micro PDF417, Codablock F, QR Code, Micro QR Code, Data Matrix (ECC 000-140 & ECC 200), Aztec Code, Aztec Runes, Chinese Sensible Code, Maxicode</p> <p>Postal Code: Chinese Post Matrix 2 of 5, Korean Postal Authority, Intelligent Mail Barcode, Postnet</p>
SCANNING CHARACTERISTICS	
Decide Rate	100 decodes/second
Light Source	650nm visible laser diode
Depth of Field	60-570 mm
Barcode Symbologies	All 1D and 2D
WARRANTY	
Return Policy	30 days
Setup Support	30 days
Manufacturer Defect Warranty	2 year