

Wisnap Adapter Specifications

PART NUMBER: RN-340

ELECTRICAL	
Power Supply	Philmore Coaxial Power Connector, No. 204 (1.3mm ID / 3.5mm OD); Center pin is positive
Battery Option	Yes
Battery Type	Recommended batteries are NiMH type with rating of 800mAh or more
Charging Method	Pin 9 serial DB9 connector, wall supply: 5 VDC @ 1A
INTERFACE	
Serial Type(s)	RS-232
Serial Interface(s)	DB9 Female (DCE), DB9 Male (DTE)
Data Rates	1200, 2400, 4800, 9600, 19.2k, 38.4k, 57.6k, 115.2k, 230k
Characters	7 or 8 Data Bits
Parity	Odd, Even, None
Stop Bits	1 or 2
Flow Control	Hardware (RTS/CTS) or None
Control Signals	CTS, RTS
Radio(s)	Class 2 Bluetooth (up to 10 meters)
Profiles	SPP, HID
Connection Modes	Master, Slave, Instant Cable Replacement
Protocols	Bluetooth 2.0 with high EDR data rate (compatible with 1.1 and 1.2)
PHYSICAL	

WiFi Radio	802.11 b/g; 2.4 GHz Full TCP/IP stack Real-time clock
ENVIRONMENT	
Operating Temperature	-40-+70 °C
COMPATIBILITY	
Operating Systems	Mac, Windows, iOS, Android
WARRANTY	
Return Policy	30 days
Setup Support	30 days
Manufacturer Defect Warranty	1 year