

Scanfob® PX20 Wireless Barcode Scanner Specifications

SKU: PX20-SF

PHYSICAL	
Power Source	Micro USB/Battery
Battery Option	Embedded
Battery Type	Lithium-Ion polymer rechargeable (600 mAh)
Charging Method	Micro USB
Charge Cycles	10,000
Charging Time	2.5 hours
Operating Time	20 hours with average scanning, 35 hours with light scanning
Dimensions	34mm x 71mm x 15mm (1.34" x 2.8" x 0.59")
Weight	40 g (1.4 oz)
Memory RAM	96 kB
Memory FlashROM	1024 kB
Keys	1 scan button, 1 function button
Real Time Clock	Quartz RTC
Microprocessor	32 bit
INTERFACE	
Bluetooth	HID, SPP, BLE
USB	Micro USB

Batch Mode	Yes
ENVIRONMENT	
Operating Temperature	0-50 °C (32-122 °F)
COMPATIBILITY	
Operating Systems	Mac, Windows, iOS, Android
Barcode Types	<p>Barcode 1D : UPC-A, UPC-A Add-on, UPC-E, UPC-E Add-on, EAN-13, EAN-13, Addon, EAN-8, EAN-8 Add-on, JAN-8, JAN-13, Code 39, Tri-Optic, Codabar (NW-7), Industrial 2 of 5, Interleaved 2 of 5, S-Code, IATA, Code 93, Code 128, MSI/Plessey, UK/Plessey, TELEPEN, Matrix 2of5, Code 11, GS1 DataBar, GS1 DataBar Limited, GS1, DataBar Expanded, Composite GS1-DataBar, Composite GS1-128, Composite EAN, Composite UPC</p> <p>Barcode 2D: PDF417, MicroPDF417, Codablock F, QR Code , Micro QR Code, DataMatrix (ECC 0 - 140 / ECC 200), MaxiCode (Modes 2 to 5), Aztec Code, Chinese Sensible Code</p> <p>Postal Code: Chinese Post, Korean Postal Authority code</p>
SCANNING CHARACTERISTICS	
Decide Rate	100 decodes/second
Light Source	Green Aiming LED, 2 illumination red LEDs
Depth of Field	60-300 mm
Barcode Symbologies	All 1D and 2D
WARRANTY	
Return Policy	30 days
Setup Support	30 days
Manufacturer Defect Warranty	2 year